

PosiFrac HALO™ —

| | | | | | | | * | | | |
|-------|-------|-------|-------|--------|-------|-------|-------|-------|----------------|--------------|
| (.) | () | (/) | (.) | () | (.) | () | (.) | () | (psi) | ° (°F) |
| 4,50 | 114,3 | 11,6 | 3,775 | 95,89 | 2,875 | 73,03 | 6,5 | 162,1 | 69 (10 000) | 177 (350) |
| 4,50 | 114,3 | 13,5 | 3,695 | 93,85 | | | | | | |
| 4,50 | 114,3 | 15,1 | 3,600 | 91,44 | | | | | | |
| 5,50 | 139,7 | 20,0 | 4,550 | 115,57 | 3,750 | 95,25 | | | | |
| 5,50 | 139,7 | 23,0 | 4,445 | 112,90 | | | | | | |
| 5,50 | 139,7 | 26,0 | 4,325 | 109,86 | 3,625 | 92,08 | | | | |

*

| | | | | | | | * | | | |
|-------|-------|-------|-------|--------|-------|--------|-------|-----------|----------------|--------------|
| (.) | () | (/) | (.) | () | (.) | () | (.) | () | (psi) | ° (°F) |
| 4,50 | 114,3 | 11,6 | 3,775 | 95,89 | 3,350 | 85,09 | 4,63 | 177, 6 | 69 (10 000) | 177 (350) |
| 4,50 | 114,3 | 13,5 | 3,695 | 93,85 | 3,270 | 83,06 | | | | |
| 4,50 | 114,3 | 15,1 | 3,600 | 91,44 | 3,176 | 80,67 | | | | |
| 5,50 | 139,7 | 20,0 | 4,550 | 115,57 | 4,128 | 104,85 | | | | |
| 5,50 | 139,7 | 23,0 | 4,445 | 112,90 | 4,020 | 102,11 | | | | |
| 5,50 | 139,7 | 26,0 | 4,325 | 109,86 | 3,898 | 99,01 | | | | |

*

HydraWell, Inc.

TAM International